

VARIABLE PASSANTE DA FILO - CORDSET DIMMER



Design: Zecca & Zecca
Comando rotativo - Rotary control



Color	Code	W <small>min. max.</small>	V	Hz	LPH <small>mm</small>		PCS	CCM cm ³
N	RL1618	60÷300	220-240	50/60	40x150x27		20	6.800



Varialuce elettronico da tavolo in classe II. Comando rotativo.
Class II electronic table dimmer. Rotary control

Comando a pulsante - Push-button control



Color	Code	W <small>min. max.</small>	V	Hz	LPH <small>mm</small>		PCS	CCM cm ³
N	RL7150	20÷160	220-240	50/60	22x83x22		20	6.800



Della dimensione di un normale interruttore spezzafilo, è un varialuce elettronico da tavolo in classe II per lampade ad incandescenza ed alogene. Comando a pulsante.
Same dimensions of a normal switch, is a dimmer for Incandescent or halogen lamps. Class II electronic table dimmer. Push-button control.

Comando a pulsante - Push-button control



Color	Code	W <small>min. max.</small>	V	Hz	LPH <small>mm</small>		PCS
N	RL0015	40÷300	220-240	50	76x95x36		12
T	RL0038	40÷300	220-240	50	76x95x36		12
P	RL0031	40÷300	220-240	50	76x95x36		12



Offerte valide fino ad esaurimento scorte - Offer valid until stock cleared

Varialuce elettronico da tavolo o pavimento in classe II. Comando a pulsante.
Electronic table or floor class II dimmer. Push button control

Design: Olaf von Bohr
Comando a cursore - Slide control



Color	Code	W <small>min. max.</small>	V	Hz	LPH <small>mm</small>		PCS	CCM cm ³
N	RL5600	60÷300	220-240	50/60	Ø94x37		1	-
N	RL1104	60÷300	220-240	50/60	71x115x39		1	-



Varialuce elettronico da tavolo o pavimento in classe II. Comando a cursore.
Electronic table or floor class II dimmer. Slide control