

VARIABLE PASSANTE DA FILO - CORDSET DIMMER



Design: Zecca & Zecca

Comando rotativo - Rotary control

RTS1



Color	Code	W min. max.	V	Hz	LPH mm	Light icon	PCS	CCM cm ³	QTY	Euro Netto
N	RL1618	60÷300	220-240	50/60	40x150x27	●	20	6.800	2.000	4,00

Offerte valide fino ad esaurimento scorte - Offer valid until stock cleared



Varialuce elettronico da tavolo in classe II. Comando rotativo.
Class II electronic table dimmer. Rotary control



Comando a pulsante - Push-button control

RH SNELLO



Color	Code	W min. max.	V	Hz	LPH mm	Light icon	PCS	CCM cm ³	Euro cad.
N	RL7150	20÷160	220-240	50/60	22x83x22	●	20	6.800	25,00



Della dimensione di un normale interruttore spezzafilo, è un varialuce elettronico da tavolo in classe II per lampade ad incandescenza ed alogene. Comando a pulsante.
Same dimensions of a normal switch, is a dimmer for Incandescent or halogen lamps. Class II electronic table dimmer. Push-button control.



Comando a pulsante - Push-button control

CROSS F



Color	Code	W min. max.	V	Hz	LPH mm	Light icon	PCS	QTY	Euro Netto
N	RL0015	40÷300	220-240	50	76x95x36	●	12	600	4,00
T	RL0038	40÷300	220-240	50	76x95x36	●	12	730	4,00
P	RL0031	40÷300	220-240	50	76x95x36	●	12	160	4,00

Offerte valide fino ad esaurimento scorte - Offer valid until stock cleared



Varialuce elettronico da tavolo o pavimento in classe II. Comando a pulsante.
Electronic table or floor class II dimmer. Push button control



Design: Olaf von Bohr

Comando a cursore - Slide control

RONDÓ



Color	Code	W min. max.	V	Hz	LPH mm	Light icon	PCS	CCM cm ³	Euro cad.
B	RL5618	60÷300	220-240	50/60	Ø94x37	●	50	29.913	22,00
T	RL5640	60÷300	220-240	50/60	Ø94x37	●	50	29.913	23,00
N	RL5600	60÷300	220-240	50/60	Ø94x37	●	1	-	21,00



Varialuce elettronico da tavolo o pavimento in classe II. Comando a cursore.
Electronic table or floor class II dimmer. Slide control

