



Proiettore da incasso, parete e plafone particolarmente adatto per magazzini, garage, stazioni di servizio e luoghi con atmosfera potenzialmente esplosiva. Completo di alimentatore elettronico.

**Installazione:** ad incasso, parete e plafone

**Corpo e telaio:** in alluminio pressofuso

**Verniciatura:** di tipo poliestere eseguita a polvere, resistente agli agenti atmosferici e alla corrosione. Colore Bianco RAL 9003.

**PG:** pressacavo in metallo M16 (cavo Ø 4÷8mm<sup>2</sup>)

**Ottica:** diffusore realizzata in PMMA resistente ai raggi UV

**Sorgente:** LED **PHILIPS** lumileds  
 Mantenimento del flusso luminoso minimo al 90% - 100.000h (L90B10) per il 90% dei LED

**Driver:** incorporato  
 Fattore di potenza ≥ 0,95.

*Recessed flood light particularly suitable for warehouses, garages, service stations and places in general with potentially explosive atmosphere. Complete with electronic ballast.*

*Installation: recessed, wall and ceiling*

*Body and frame: die cast aluminum*

*Coating: coated with powdered polyester, resistant to atmospheric agents and corrosion. White colour RAL 9003*

*PG: M16 metal cable gland (cable 4÷8mm<sup>2</sup>)*

*Optic: wide made of UV-resistant PMMA*


*Light source: LED **PHILIPS** lumileds  
 Maintenance of minimum luminous flux to 90% - 100.000h (L90B10) for 90% of LED.*

*Driver: certified.  
 Power factor ≥ 0,95.*

**Use:** the light fitting is suitable for the environment with a danger of explosion of gas, dust and combustible fumes. The light fittings meet the requirements of Government Decree 116/2016 Coll. and European Community Directive N°. 2014/34/EU.




**100.000 h** L90B10



	100-277 Vac	50/60 Hz	IP66
IK10	CRI >70		850°

colour	W	Led SMD	angle	K	nominal Im tc = 25°C	Im output	lm/W	pcs	Kg	CELL
[B]	100	LED Smd 3030	120°	4000	18.400	16.000	160	1	4,00	RL04-100
[B]	150	LED Smd 3030	120°	4000	26.700	23.250	155	1	4,00	RL04-150



Protezione contro le atmosfere esplosive <i>Protection against explosive atmospheres</i>	II 2G Ex ib IIC T6
Zona pericolosa ammessa <i>Hazardous area allowed</i>	Zona 2 - Zone 2 Zona 22 - Zone 22
Normative di riferimento <i>Standard references</i>	EN 60079-0:2012/A11:2013 EN 60079-11:2012 EN60079-31:2014

**Accessori non inclusi - Not included accessories**



Cod. RL04/PL  
 Accessorio per installazione a plafone  
 Accessory for ceiling installation



Cod. RL04/R  
 Accessorio per installazione a incasso  
 Accessory for recessed installation



Cod. RL04/S  
 Accessorio staffa  
 Bracket accessory



Cod. 703952.NEW  
 Attacco palo per 1 o 2 proiettori, Ø60/76mm  
 Pole attachment for either 1 or 2 floodlights, size Ø 60/76mm.

Floodlight