

LED Audace C-W-R



Serie di proiettori a plafone (C), parete (W) o semincasso (R) orientabili progettati per illuminare ambienti dove è necessaria un'illuminazione generale e d'accento.

Installazione: a soffitto e/o parete.

Corpo: in alluminio pressofuso UNI 5076, verniciato con polvere termoindurente poliestere.

Verniciatura: di tipo poliestere eseguita a polvere.

Colore nero RAL 9005 o Bianco RAL 9010.

Ottica: semi concentrante a 36° (a richiesta 12°, 24° o 45°).

Schermo: vetro temperato di spessore 3mm.

Driver: dimmerabile 0-10V. incorporato (versioni W/C)

Conforme alla norma: EN60598-1, RG0 nessun rischio fotobiologico ai fini della norma EN62471.

Led: LUMILEDS - PHILIPS mantenimento del flusso luminoso minimo al 80%: 50.000h (L80B10).

Series of ceiling or semi-recessed adjustable projectors designed to light up place that requires general and spot lighting.

Installation: ceiling and / or wall.

Body: made by UNI 5076 die-cast aluminum, coated with polyester thermoset powder.

Coating: coated with powdered polyester. RAL 9005 black or RAL 9010 white color.

Optic: semi-clumping at 36° (on request 12°, 24° o 45°).

Shield: tempered glass with 3mm thickness.

Driver: dimmable 0-10V included (W/C version).

According to standard: EN60598-1, RG0 exempt from photo-biological risks in compliance with standard EN62471.



Led: LUMILEDS - PHILIPS maintenance of minimum luminous flux to 80%: 50.000h (L80B10).

Orientabilità - Adjustability



220-240V 50/60Hz **IK07** **IP20**

LED Audace C-W




	colour	W		lm output	K		pcs	Kg	CELL
0-10V	B	32	Led COB	3840	3000	40°	001	1,44	32928/010
0-10V	B	32	Led COB	3840	4000	40°	001	1,44	32928/010/4K
0-10V	N	32	Led COB	3840	3000	40°	001	1,44	32929/010
0-10V	N	32	Led COB	3840	4000	40°	001	1,44	32929/010/4K



220-240V 50/60Hz **IK07** **IP20**

LED Audace R



	colour	W		lm output	K		pcs	Kg	CELL
0-10V	B	32	Led COB	3840	3000	40°	001	1,44	32930/010
0-10V	B	32	Led COB	3840	4000	40°	001	1,44	32930/010/4K
DALI 2 PUSH	B	32	Led COB	3840	3000	40°	001	1,44	32930/DA
DALI 2 PUSH	B	32	Led COB	3840	4000	40°	001	1,44	32930/DA/4K



Recessed/ceiling/wall