

LED Beautylight

A richiesta
On demand

0-10V



IP65

Faretto LED ad incasso in alluminio pressofuso con diverse finiture con schermo in vetro satinato, grado IP65. Idoneo per applicazioni in zone umide, ottimo il suo utilizzo in centri benessere, laddove si necessiti di un grado IP elevato.

Installazione: incasso a soffitto.

Corpo: alluminio pressofuso.

Orientabilità: fisso.

Verniciatura: di tipo poliestere, eseguita a polvere bianco RAL 9010.

Cablaggio: rapido, come da foto.

Conforme alla norma: EN60598-1, RG0 nessun rischio fotobiologico ai fini della norma EN62471.

Led: mantenimento del flusso luminoso minimo al 80%: 50.000h (L80B10).

Driver: incluso nel Kit.

Recessed LED spotlight in die cast aluminium with different finishes with satin-finish glass screen, protection rating IP65. Suitable for applications in humid areas, ideal for use in well-being facilities, requiring a high IP rating.

Installation: ceiling recessed

Body: die cast aluminium

Adjustable: vertical 45°

Coating: coated with powered polyester white RAL 9010.

Wiring: fast, like a photo.

According to standard: EN60598-1, RG0 exempt from photo-biological risks in compliance with standard EN62471.

Led: maintenance of minimum luminous flux to 80%: 50.000h (L80B10).



Driver: included in Kit.

220-240V 50/60Hz



IK03

IP65



CRI 90

DRIVER INCLUDED
MULTIPOWER



colour	W max			mA	Lm	K	pcs	Kg	CELL
[B]	8	3 Led SMD	40°	700	800	3000	010	0.60	30611NAPO
[B]	13	Led SMD	40°	350	1400	3000	010	0.60	30611/VL
[B]	8	3 Led SMD	40°	700	800	3000	010	0.60	30611NAPODA
[B]	13	Led SMD	40°	350	1400	3000	010	0.60	30611/VLDA

A richiesta: versione 4000K aggiungere 4 dopo il codice - **On demand:** 4000K versions add 4 after the code



Recessed

