



LED Sud



Norme di riferimento
Standard reference
 EN60598-1
 EN60598-2-1
 EN62471
 EN62031
 EN60598-2-5
 EN61547



Paletto per l'illuminazione di giardini o parchi, con doppia ottica idonea per l'illuminazione di camminamenti o aiuole.

Installazione: terra

Corpo: in alluminio pressofuso UNI EN 1706, verniciato con polvere termoindurente poliesteri

Verniciatura: di tipo poliesteri eseguita a polvere, resistente agli agenti atmosferici e alla corrosione e garantita per 1.000 ore in nebbia salina. Colore Antracite.

Diffusore: in policarbonato opalino

Portalampane: GU10

Sorgente: non inclusa, da ordinare separatamente.

Lighting bollard suitable for installation in gardens or parks, with double optics, suitable for lighting walkways or flower beds.

Installation: on ground

Housing: made by UNI EN 1706 die-cast aluminum, coated with polyester thermoset powder

Coating: coated with powdered polyester, resistant to atmospheric agents, corrosion and guaranteed for 1.000 hours in saline mist. Black RAL9005 color.

Diffuser: made by frosted polycarbonate.

Lampholder: GU10.

Light source: not included, to be ordered separately.

220-240 Vac	50/60 Hz	IP65	IK09	+40°C -20°C	850°	CE
-------------	----------	------	------	----------------	------	----



colour	H mm	W	Portalampane	pcs	Kg	S
N	440	max 7W	GU10	1	1,50	25001

Sorgente luminosa NON INCLUSA da ordinare a parte Light source NOT INCLUDED to be ordered separately									
W	V	Portalampane	K	lm	Ra	ON/OFF	Code		
7≈(50)	220-240	GU10	3000	A+	700	80	15.000	25.000	555257.0101
7≈(50)	220-240	GU10	4000	A+	700	80	15.000	25.000	555279.0101



Outdoor