

# PLATAX E27

Plafoniera compatta stagna idonea per applicazioni civili, commerciali, alberghiere ed ovunque siano richieste caratteristiche di protezione contro l'ingresso di polveri o liquidi.

**Corpo e cornice:** in nylon rinforzato con fibre di vetro, guarnizione in silicone, vite-ri-a impermeabile.

**Riflettore:** in alluminio stampato.

**Diffusore:** in policarbonato opale antiurto ed autoestinguento.

**Cablaggio:** alimentazione 220/240V 50/60Hz, cavo non infiammabile HT105°, morsettiere in nylon.

Platax è installabile sia per impianto sotto parete che esterno; l'ingresso cavo è predisposto per un serracavo di diametro 16 mm. Confezione: termo-retraibile.

*Compact waterproof fitting suitable for public areas, halls, hotels, passages etc. where dust and water protection is necessary.*

**Casing and frame:** nylon reinforced fibreglass, silicon gasket, non-loosening screws. **Reflector:** Pressed aluminium. **Diffuser:** Self-extinguishing opal shockproof polycarbonate.

**Wiring:** 220/240V 50/60Hz power supply, HT105° non-flammable cable, nylon connector block.

*The cable entry is predisposed for a 16 mm cable gland.*

*Packaging: thermoretractable film.*




220-240V 50/60Hz **IK09** **IP65**

## Platax E27



colour	Lampholder	V	pcs	Kg	S
<b>B</b>	E27	220-240	006	0,70	702198.0101
<b>N</b>	E27	220-240	006	0,70	702206.0101
<b>B</b>	2xE27	220-240	006	0,70	702199.0101

### Accessori - Accessories



**B** Cod. CO3001.100  
Ø 290mm  
Visiera Nylon - Nylon visor

**N** Cod. CO3002.100  
Ø 290mm (Platax)  
Visiera Nylon - Nylon visor

### Lampada non inclusa - Not included lamp



W	V			K		Im	Ra	DIM			H mm	Ø mm	Code
8=(60)	220-240	E27	360°	3000	A	800	80	SI	15.000	25.000	105	60	555286.0101
8=(60)	220-240	E27	360°	4000	A	800	80	NO	15.000	25.000	105	60	555286.4K
10=(100)	220-240	E27	360°	3000	A+	1000	80	SI	15.000	25.000	105	60	555383.0101
10=(100)	220-240	E27	360°	4000	A+	1000	80	NO	15.000	25.000	105	60	555383.4K

