



## TECHNICAL SHEET

Selfcontained emergency led luminaire

Modello: **ORIONE**  
1948



**Relco**  
GROUP



IP42

### Description

ORIONE IP42 18 SE 1H V X

### Technical characteristics

- Green signaling led
- Mains: 220-240Vac 50-60 Hz
- Energy consumption: 1,6W
- Type: SE (Non maintained)
- Mean emergency flux: 320 Lumen
- Minimum emergency flux: 315 Lumen
- Batteria: LiFePO4 3,2V 1,5Ah
- Recharge time: 24h
- Duration: 1h / 2h \*
- Inhibition: NO
- Insulation class: II
- IP grade: IP42. IP65 with RO0338IP
- Working temperature: 0 °C to 40 °C
- Signaling visibility with pictogram (EN1838): 18 m
- Photobiological risk exempt (EN62471)
- Compliant to RoHS2: 2011/65/UE; 2015/863
- Installation: wall, ceiling, flag
- Glow wire 850 °C
- Warranty: 2 years, battery 4 years
- Weight: 0,2 Kg

\* 2 hours 160 Lumen

### Reference standards

EN60598-1, EN60598-2-2, EN60598-2-22, EN61347-1, EN61347-2-13, EN62031, EN62384

### Luminous source

- Type: LED
- Nr. 12 0,5W Led
- Color temperature: 6000K

RELCO S.r.l. via delle Azalee 6/A, 20090 Buccinasco - Milano, UNI EN ISO 9001 certified

*Relco S.r.l. pursues a policy of continuous research and development, therefore reserves the right to vary the characteristics of the products at any time and without notice for manufacturing needs or for product improvement..*